

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
FX Sport	50cm	700c	45.0	74.6 °	13.0	71.1 °	51.9		8.0	42.0	5.3	6.0	99.6	71.6	36.8	54.6
	52cm	700c	47.5	74.2 °	14.5	71.3 °	53.0		8.0	42.0	5.3	5.9	100.3	73.5	37.1	56.1
	54cm	700c	50.0	73.7 °	16.0	71.3 °	54.2		8.0	42.0	5.3	5.9	101.0	75.4	37.4	57.5
	56cm	700c	52.5	73.3 °	17.5	71.9 °	55.4		7.8	42.0	4.8	6.1	100.8	77.6	37.7	59.1
	58cm	700c	54.8	73.0 °	19.5	72.0 °	56.7		7.8	42.5	4.8	6.0	102.2	79.6	38.0	61.1
	60cm	700c	56.7	72.8 °	22.0	72.1 °	57.9		7.5	42.5	4.8	5.9	103.2	81.7	38.3	63.2
FX 4	15"	700c	38.1	74.5 °	11.5	70.5 °	54.4	28.5		44.5	5.0	7.0	105.7	69.3		
FX 3	17.5"	700c	44.4	74.0 °	13.0	70.5 °	54.8	28.5		44.5	5.0	7.0	105.7	73.5		
	20"	700c	50.8	73.5 °	16.0	71.5 °	56.8	28.5		44.5	4.5	7.0	105.8	78.3		
	22.5"	700c	57.1	73.0 °	19.0	72.5 °	59.0	28.5		44.5	4.5	6.2	106.4	83.1		
	25"	700c	63.5	72.0 °	22.0	72.5 °	60.3	28.5		44.5	4.5	6.2	106.5	87.7		
FX 2	15"	700c	38.1	74.5 °	11.5	70.5 °	54.4	28.5		44.5	5.0	7.1	105.6	69.7		
FX 1	17.5"	700c	44.4	74.0 °	13.0	70.5 °	54.8	28.5		44.5	5.0	7.1	105.6	73.8		
	20"	700c	50.8	73.5 °	16.0	71.5 °	56.8	28.5		44.5	4.5	7.0	105.7	78.6		
	22.5"	700c	57.1	73.0 °	19.0	72.5 °	59.0	28.5		44.5	4.5	6.3	106.3	83.4		
	25"	700c	63.5	72.0 °	22.0	72.5 °	60.3	28.5		44.5	4.5	6.3	106.4	88.0		
	15" Stagger	700c	38.1	74.5 °	13.0	70.5 °	54.3	28.5		44.5	5.0	7.1	105.6	62.7		
	17.5" Stagger	700c	44.5	74.0 °	15.0	70.5 °	54.8	28.5		44.5	5.0	7.1	105.7	63.2		
	20" Stagger	700c	50.8	73.5 °	17.0	71.5 °	56.8	28.5		44.5	4.5	7.0	105.7	63.6		
	22.5" Stagger	700c	57.2	73.0 °	19.0	72.5 °	58.5	28.5		44.5	4.5	6.3	106.3	64.0		
FX Women's	13"	700c	33.0	75.0 °	11.5	70.0 °	53.0	28.5		44.5	5.0	7.3	105.3	66.6		
	15"	700c	38.1	75.0 °	13.0	70.5 °	53.3	28.5		44.5	5.0	7.0	105.3	69.7		
	17"	700c	43.2	74.5 °	15.0	70.5 °	53.9	28.5		44.5	5.0	7.0	105.5	73.2		
	19"	700c	48.3	74.0 °	16.0	70.5 °	55.3	28.5		44.5	5.0	7.0	106.4	76.7		
	15" Stagger	700c	38.1	74.5 °	13.0	70.5 °	54.3	28.5		44.5	5.0	7.0	105.6	62.4		
	17.5" Stagger	700c	44.5	74.0 °	15.0	70.5 °	54.8	28.5		44.5	5.0	7.0	105.7	63.0		
	20" Stagger	700c	50.8	73.5 °	17.0	71.5 °	56.8	28.5		44.5	4.5	7.0	105.7	63.3		
Zektor	50cm	700c	50.0	74.5 °	12.3	72.0 °	52.6	29.4	6.5	43.7	5.0	6.4	101.6	77.8	37.5	54.3
	53cm	700c	53.0	74.0 °	14.3	72.0 °	54.0	29.4	6.5	43.7	5.0	6.4	102.5	80.1	37.8	56.2
	56cm	700c	56.0	73.5 °	16.3	72.0 °	56.0	29.4	6.5	43.7	5.0	6.4	104.0	82.4	38.7	58.1
	61cm	700c	61.0	72.5 °	20.3	72.0 °	59.5	29.4	6.5	43.7	5.0	6.4	106.5	86.8	40.0	61.9
	50cm Stagger	700c	50.0	74.5 °	12.0	72.0 °	52.5	29.4	6.5	43.7	5.0	6.4	101.5	62.7	37.5	54.0
	53cm Stagger	700c	53.0	74.0 °	14.0	72.0 °	53.9	29.4	6.5	43.7	5.0	6.4	102.4	62.0	37.8	55.9
	56cm Stagger	700c	56.0	73.5 °	16.0	72.0 °	55.9	29.4	6.5	43.7	5.0	6.4	103.9	60.8	38.7	57.8
DS Series	15.5"	700c	36.6	74.5 °	11.4	70.0 °	57.5	29.4		45.5	3.8	8.5	109.1	73.8		
	17.5"	700c	41.7	74.0 °	12.4	71.0 °	59.0	29.4		45.5	3.8	8.2	109.5	76.1		
	19"	700c	46.7	73.5 °	13.4	71.0 °	60.5	29.4		45.5	3.8	8.2	110.5	79.1		
	21"	700c	50.5	73.0 °	14.4	71.5 °	62.0	29.4		45.5	3.8	7.8	111.0	81.5		
	22.5"	700c	54.3	72.5 °	15.4	72.0 °	63.5	29.4		45.5	3.8	7.5	111.2	84.1		
Neko Women's	14"	700c	33.8	74.5 °	11.4	70.0 °	55.0	29.4		45.5	3.8	8.9	107.0	69.4		
	16"	700c	38.2	74.0 °	11.4	70.5 °	56.0	29.4		45.5	3.8	8.5	107.0	71.6		
	18"	700c	43.3	73.5 °	12.4	71.0 °	57.5	29.4		45.5	3.8	8.2	107.5	74.5		
	14" Stagger	700c	35.6	74.5 °	13.4	70.0 °	55.0	29.4		45.5	3.8	8.9	107.0	62.2		
	16" Stagger	700c	38.2	74.0 °	13.4	70.5 °	56.0	29.4		45.5	3.8	8.5	107.0	62.2		
	18" Stagger	700c	43.3	73.5 °	14.4	71.0 °	57.5	29.4		45.5	3.8	8.2	107.6	62.2		
Lync	15"	700c	38.1	74.5 °	12.5	70.5 °	54.7	28.4		44.5	4.5	7.6	105.5	70.0		
	17.5"	700c	44.4	74.0 °	14.0	70.5 °	54.8	28.4		44.5	4.5	7.6	105.2	74.1		
	20"	700c	50.8	73.5 °	16.0	71.5 °	56.5	28.4		44.5	4.5	6.9	105.3	78.5		
	22.5"	700c	57.2	73.0 °	18.0	72.5 °	58.1	28.4		44.5	4.5	6.3	105.4	81.6		
	25"	700c	63.5	72.0 °	20.0	72.5 °	59.2	28.4		44.5	4.5	6.3	105.3	85.9		
CrossRip	49cm	700c	49.0	75.0 °	11.5	69.9 °	52.2	27.7	7.4	43.5	5.0	7.6	103.1	73.9	37.6	53.6
	52cm	700c	52.0	74.0 °	12.1	70.5 °	52.4	27.7	7.4	43.5	5.0	7.2	103.7	75.6	38.7	56.0
	54cm	700c	54.0	73.5 °	14.3	70.5 °	55.4	27.7	7.4	43.5	5.0	7.2	104.3	77.5	39.6	58.2
	56cm	700c	56.0	73.0 °	16.0	71.0 °	57.0	28.1	7.0	43.5	5.0	6.9	105.1	79.4	40.2	59.6
	58cm	700c	58.0	73.0 °	17.3	71.5 °	57.8	28.1	7.0	43.5	5.0	6.9	105.4	81.0	40.6	61.1
	61cm	700c	61.0	72.5 °	19.3	71.5 °	59.4	28.1	7.0	43.5	5.0	6.6	106.5	83.4	41.0	63.0
Super Commuter+	45cm	700c	40.0	73.0°	13.0	69.0°	55.9	29.9	6.0	47.0	4.5	8.9	109.6	75.6	38.0	58.6
	50cm	700c	45.0	73.0°	15.0	69.5°	57.4	29.9	6.0	47.0	4.5	8.6	110.7	78.9	38.8	60.7
	55cm	700c	50.0	73.0°	17.5	70.0°	59.0	29.9	6.0	47.0	4.5	8.3	111.9	81.6	39.7	63.3
	60cm	700c	55.0	73.0°	20.5	70.5°	61.3	29.9	6.0	47.0	4.5	7.9	113.8	85.1	41.0	66.3
XM700+	50cm	700c		73.0 °		70.5 °	57.6	29.9	6.0	47.5	4.5	7.9	110.3	80.0	38.8	
	55cm	700c		73.0 °		71.0 °	59.2	29.9	6.0	47.5	4.5	7.6	111.5	83.7	39.7	
	60cm	700c		73.0 °		71.5 °	61.5	29.9	6.0	47.5	4.5	7.3	113.3	87.7	41.0	
	45cm Lowstep	700c		73.5 °		70.0 °	56.1	29.9	6.0	47.5	4.5	8.3	109.8		38.5	
	50cm Lowstep	700c		73.0 °		70.5 °	57.6	29.9	6.0	47.5	4.5	7.9	110.3		38.8	
	55cm Lowstep	700c		73.0 °		71.0 °	59.2	29.9	6.0	47.5	4.5	7.6	111.5		39.7	

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
Conduit+	15"		38.1	74.5 °	13.2	70.5 °	54.7	28.9		46.5	4.5			70.9	39.1	56.0
	17.5"		44.4	74.0 °	14.7	70.5 °	54.8	28.9		46.5	4.5			74.9	38.4	57.4
	20"		50.8	73.5 °	16.7	71.5 °	56.4	28.9		46.5	4.5			79.1	38.8	59.7
	22.5"		57.1	73.0 °	18.7	72.5 °	58.1	28.9		46.5	4.5			83.5	39.2	62.0
Lift+	13.5"	26in	42.0	65.5 °	21.0	69.5 °	61.2	28.6		49.5	5.0	7.3	109.0	69.5	34.0	59.8
	16.5"	26in	45.7	65.5 °	21.0	69.5 °	62.0	28.6		49.5	5.0	7.3	109.8	71.7	34.7	59.8
	21"	26in	53.3	65.5 °	26.0	69.5 °	65.0	28.6		49.5	5.0	7.3	112.3	78.0	35.5	64.5
	13.5" Lowstep	26in	34.3	65.5 °	20.0	69.5 °	59.2	28.6		49.5	5.0	7.3	107.1	64.4	32.4	58.9
	16.5" Lowstep	26in	42.0	65.5 °	21.0	69.5 °	61.2	28.6		49.5	5.0	7.3	109.0	69.1	34.0	59.8
Dual Sport+	15"	700c	39.3	74.5 °	11.4	70.0 °	57.5	28.8	6.6	46.5	3.8	7.8	110.5	71.9	40.9	59.8
	17.5"	700c	44.5	74.0 °	12.4	71.0 °	59.0	28.8	6.6	46.5	3.8	7.4	111.0	74.9	41.5	61.0
	20"	700c	48.3	73.5 °	13.4	71.0 °	60.5	28.8	6.6	46.5	3.8	7.4	112.0	77.2	42.1	61.9
	22.5"	700c	53.3	73.0 °	14.4	71.5 °	62.0	28.8	6.6	46.5	3.8	7.1	112.4	80.4	42.7	63.1
	25"	700c	57.1	72.5 °	15.4	72.0 °	63.5	28.8	6.6	46.5	3.8	6.8	112.7	83.0	43.3	64.2
Neko+ Women's	14"	700c	35.5	74.5 °	11.4	70.0 °	55.0	28.8	6.6	46.5	3.8	8.7	107.8	67.8	38.4	59.8
	16"	700c	40.6	74.0 °	11.4	70.5 °	56.0	28.8	6.6	46.5	3.8	8.5	107.8	70.3	38.8	60.0
	18"	700c	45.7	73.5 °	12.4	71.0 °	57.5	28.8	6.6	46.5	3.8	8.2	108.2	73.0	39.4	61.2
Verve	15"	700c	38.1	71.0°	8.5	71.0 °	57.6	29.2	7.0	46.5	5.5	6.6	107.0	68.4		
	17.5"	700c	44.5	70.5°	10.0	71.5 °	58.7	29.2	7.0	46.5	5.5	6.3	107.0	72.4		
	20"	700c	46.5	70.0°	14.0	71.5 °	60.6	29.2	7.0	46.5	5.5	6.3	108.3	77.3		
	22.5"	700c	46.5	70.0°	16.5	71.5 °	62.0	29.2	7.0	46.5	5.5	6.3	109.6	82.0		
Verve Women's	13"	700c	33.0	72.0°	14.5	71.5 °	56.4	29.2	7.0	46.5	5.5	6.6	107.0	68.9	37.5	58.2
	16"	700c	40.6	71.0°	15.5	71.5 °	58.9	29.2	7.0	46.5	5.5	6.3	107.8	72.6	38.5	59.4
	19"	700c	48.3	71.0°	15.5	71.5 °	59.9	29.2	7.0	46.5	5.5	6.3	108.8	76.6	39.5	59.4
	21"	700c	53.3	70.0°	20.5	71.5 °	62.8	29.2	7.0	46.5	5.5	6.3	110.4	80.8	39.5	64.1