

Models	Frame Size Number	Dimensions											
		Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover
7.9 FX	50cm	700c	45.0	74.6 °	13.0	71.1 °	51.9		42.0	5.3	6.0	99.6	71.6
7.7 FX	52cm	700c	47.5	74.2 °	14.5	71.3 °	53.0		42.0	5.3	5.9	100.3	73.5
	54cm	700c	50.0	73.7 °	16.0	71.3 °	54.2		42.0	5.3	5.9	101.0	75.4
	56cm	700c	52.5	73.3 °	17.5	71.9 °	55.4		42.0	4.8	6.1	100.8	77.6
	58cm	700c	54.8	73.0 °	19.5	72.0 °	56.7		42.5	4.8	6.0	102.2	79.6
	60cm	700c	56.7	72.8 °	22.0	72.1 °	57.9		42.5	4.8	5.9	103.2	81.7
7.5 FX	15"	700c	38.1	74.5 °	11.5	70.5 °	54.4	28.5	44.5	5.0	7.0	105.7	69.3
7.4 FX	17.5"	700c	44.4	74.0 °	13.0	70.5 °	54.8	28.5	44.5	5.0	7.0	105.7	73.5
7.3 FX	20"	700c	50.8	73.5 °	16.0	71.5 °	56.8	28.5	44.5	4.5	7.0	105.8	78.3
	22.5"	700c	57.1	73.0 °	19.0	72.5 °	59.0	28.5	44.5	4.5	6.2	106.4	83.1
	25"	700c	63.5	72.0 °	22.0	72.5 °	60.3	28.5	44.5	4.5	6.2	106.5	87.7
7.5 FX WSD	13"	700c	33.0	75.0 °	11.5	70.0 °	53.0	28.5	44.5	5.0	7.3	105.3	66.6
7.4 FX WSD	15"	700c	38.1	75.0 °	13.0	70.5 °	53.3	28.5	44.5	5.0	7.0	105.3	69.7
7.3 FX WSD	17"	700c	43.2	74.5 °	15.0	70.5 °	53.9	28.5	44.5	5.0	7.0	105.5	73.2
7.2 FX WSD	19"	700c	48.3	74.0 °	16.0	70.5 °	55.3	28.5	44.5	5.0	7.0	106.4	76.7
	15" Stagger	700c	38.1	74.5 °	13.0	70.5 °	54.3	28.5	44.5	5.0	7.0	105.6	62.4
	17.5" Stagger	700c	44.5	74.0 °	15.0	70.5 °	54.8	28.5	44.5	5.0	7.0	105.7	63.0
	20" Stagger	700c	50.8	73.5 °	17.0	71.5 °	56.8	28.5	44.5	4.5	7.0	105.7	63.3
7.2 FX	15"	700c	38.1	74.5 °	11.5	70.5 °	54.4	28.5	44.5	5.0	7.1	105.6	69.7
7.1 FX	17.5"	700c	44.4	74.0 °	13.0	70.5 °	54.8	28.5	44.5	5.0	7.1	105.6	73.8
7.0 FX	20"	700c	50.8	73.5 °	16.0	71.5 °	56.8	28.5	44.5	4.5	7.0	105.7	78.6
	22.5"	700c	57.1	73.0 °	19.0	72.5 °	59.0	28.5	44.5	4.5	6.3	106.3	83.4
	25"	700c	63.5	72.0 °	22.0	72.5 °	60.3	28.5	44.5	4.5	6.3	106.4	88.0
	15" Stagger	700c	38.1	74.5 °	13.0	70.5 °	54.3	28.5	44.5	5.0	7.1	105.6	62.7
	17.5" Stagger	700c	44.5	74.0 °	15.0	70.5 °	54.8	28.5	44.5	5.0	7.1	105.7	63.2
	20" Stagger	700c	50.8	73.5 °	17.0	71.5 °	56.8	28.5	44.5	4.5	7.0	105.7	63.6
	22.5" Stagger	700c	57.2	73.0 °	19.0	72.5 °	58.5	28.5	44.5	4.5	6.3	106.3	64.0
DS Series	15.5"	700c	36.6	74.5 °	11.4	70.0 °	57.5	29.4	45.5	3.8	8.5	109.1	73.8
	17.5"	700c	41.7	74.0 °	12.4	71.0 °	59.0	29.4	45.5	3.8	8.2	109.5	76.1
	19"	700c	46.7	73.5 °	13.4	71.0 °	60.5	29.4	45.5	3.8	8.2	110.5	79.1
	21"	700c	50.5	73.0 °	14.4	71.5 °	62.0	29.4	45.5	3.8	7.8	111.0	81.5
	22.5"	700c	54.3	72.5 °	15.4	72.0 °	63.5	29.4	45.5	3.8	7.5	111.2	84.1
Neko	14"	700c	33.8	74.5 °	11.4	70.0 °	55.0	29.4	45.5	3.8	8.9	107.0	69.4
	16"	700c	38.2	74.0 °	11.4	70.5 °	56.0	29.4	45.5	3.8	8.5	107.0	71.6
	18"	700c	43.3	73.5 °	12.4	71.0 °	57.5	29.4	45.5	3.8	8.2	107.5	74.5
	14"	700c	35.6	74.5 °	13.4	70.0 °	55.0	29.4	45.5	3.8	8.9	107.0	62.2
	16"	700c	38.2	74.0 °	13.4	70.5 °	56.0	29.4	45.5	3.8	8.5	107.0	62.2
	18"	700c	43.3	73.5 °	14.4	71.0 °	57.5	29.4	45.5	3.8	8.2	107.6	62.2
Chelsea	49cm	700c	49.0	74.6 °	11.4	70.7 °	53.3	27.7	43.5	4.5	7.5	102.5	64.6
	53cm	700c	53.0	73.8 °	13.3	71.2 °	55.3	27.7	43.5	4.5	7.2	103.3	64.3
	56cm	700c	56.0	73.0 °	15.5	72.0 °	57.3	27.7	43.5	4.5	6.7	103.5	64.3
District 8	50cm	700c	50.0	74.5 °	11.8	71.0 °	53.7	27.7	43.8	4.5	7.5	103	75.8
Steel District	54cm	700c	54.0	73.5 °	13.8	71.5 °	56.0	27.7	43.8	4.5	7.0	103.4	79.3
	57cm	700c	57	73.0 °	16.2	72.0 °	57.7	28.1	43.8	4.5	6.7	104.5	82.4
	61cm	700c	61.0	72.5 °	18.8	72.5 °	59.8	28.1	43.8	4.5	6.4	105.3	86.2
Lync	15"	700c	38.1	74.5 °	12.5	70.5 °	54.7	28.4	44.5	4.5	7.6	105.5	70.0
	17.5"	700c	44.4	74.0 °	14.0	70.5 °	54.8	28.4	44.5	4.5	7.6	105.2	74.1
	20"	700c	50.8	73.5 °	16.0	71.5 °	56.5	28.4	44.5	4.5	6.9	105.3	78.5
	22.5"	700c	57.2	73.0 °	18.0	72.5 °	58.1	28.4	44.5	4.5	6.3	105.4	81.6
	25"	700c	63.5	72.0 °	20.0	72.5 °	59.2	28.4	44.5	4.5	6.3	105.3	85.9

CrossRip	49cm	700c	50.0	74.5 °	10.5	70.6 °	52.5	27.7	43.5	4.5	7.6	101.5	73.1
	52cm	700c	52.0	74.0 °	12.8	71.2 °	54.8	27.7	43.5	4.5	7.2	102.9	75.3
	54cm	700c	54.0	73.5 °	15.0	71.5 °	56.9	27.7	43.5	4.5	7.0	104.2	76.7
	56cm	700c	56.0	73.0 °	16.7	72.0 °	58.4	28.1	43.5	4.5	6.7	105.0	78.7
	58cm	700c	58.0	73.0 °	18.0	72.5 °	59.3	28.1	43.5	4.5	6.4	105.3	80.1
	61cm	700c	61.0	72.5 °	20.0	72.5 °	60.9	28.1	43.5	4.5	6.4	106.3	82.6
Allant	15"	700c	38.1	74.5 °	11.5	70.5 °	54.4	28.5	44.5	5.0	7.1	105.6	69.7
	17.5"	700c	44.4	74.0 °	13.0	70.5 °	54.8	28.5	44.5	5.0	7.1	105.6	73.8
	20"	700c	50.8	73.5 °	16.0	71.5 °	56.8	28.5	44.5	4.5	7.0	105.7	78.6
	22.5"	700c	57.1	73.0 °	19.0	72.5 °	59.0	28.5	44.5	4.5	6.3	106.3	83.4
920	49cm	29"	44.0	74.5 °	9.5	70.0 °	54.0	28.3	46.5	5.5	7.5	107.2	72.2
	52cm	29"	47.0	74.0 °	10.5	70.5 °	55.1	28.3	46.5	5.5	7.2	107.4	74.3
	54cm	29"	49.0	73.8 °	12.0	71.0 °	56.2	28.3	46.5	5.5	6.8	107.9	76.0
	56cm	29"	51.0	73.3 °	14.5	71.3 °	57.8	28.3	46.5	5.5	6.7	108.8	77.8
	58cm	29"	59.4	73.0 °	16.5	71.3 °	59.4	28.3	46.5	5.5	6.7	110.0	79.6
	61cm	29"	60.4	72.8 °	18.0	71.5 °	60.4	28.3	46.5	5.5	6.5	110.7	81.7
720	49cm	700c	46.6	74.2 °	9.6	70.8 °	52.6	27.4	42.6	4.5	7.4	100.2	73.3
	52cm	700c	48.6	74.0 °	11.0	71.4 °	53.8	27.4	42.6	4.5	7.0	100.7	75.0
	54cm	700c	50.6	73.7 °	12.8	71.8 °	55.0	27.6	42.6	4.5	6.7	101.4	77.0
	56cm	700c	52.6	73.5 °	14.5	72.2 °	56.3	27.6	42.6	4.5	6.5	102.1	78.6
	58cm	700c	54.6	73.3 °	16.4	72.5 °	57.5	27.8	42.6	4.5	6.3	102.9	80.5
	61cm	700c	56.6	73.0 °	19.0	72.8 °	59.3	27.8	42.6	4.5	6.0	104.1	82.5
520 Disc 520	48cm	700c	44.0	74.3 °	11.5	69.5 °	52.0	27.4	45.0	5.2	7.4	104.1	71.3
	51cm	700c	48.2	74.0 °	12.5	70.0 °	53.1	27.4	45.0	5.2	7.1	104.5	74.1
	54cm	700c	51.2	73.8 °	14.0	71.0 °	54.3	27.8	45.0	5.2	6.5	104.8	76.8
	57cm	700c	54.3	73.5 °	16.0	71.8 °	55.7	27.8	45.0	5.2	5.9	105.2	79.4
	60cm	700c	57.5	73.0 °	20.0	71.8 °	58.3	27.8	45.0	5.2	5.9	107.4	82.6
	63cm	700c	60.5	72.8 °	23.0	72.3 °	60.3	27.8	45.0	5.2	5.6	108.6	85.4
Conduit+	15"	700c	38.1	74.5 °	13.2	70.5 °	54.7	28.9	46.5	4.5	7.8	107.5	709.1
	17.5"	700c	44.4	74.0 °	14.7	70.5 °	54.8	28.9	46.5	4.5	7.8	107.2	748.7
	20"	700c	50.8	73.5 °	16.7	71.5 °	56.4	28.9	46.5	4.5	7.1	107.3	791.4
	22.5"	700c	57.1	73.0 °	18.7	72.5 °	58.1	28.9	46.5	4.5	6.5	107.4	835.5
XM700+	50cm	700c		73.0 °		70.5 °	57.6	29.9	47.5	4.5	7.9	110.3	
	55cm	700c		73.0 °		71.0 °	59.2	29.9	47.5	4.5	7.6	111.5	
	60cm	700c		73.0 °		71.5 °	61.5	29.9	47.5	4.5	7.3	113.3	
	45cm	700c		73.5 °		70.0 °	56.1	29.9	47.5	4.5	8.3	109.8	
	50cm	700c		73.0 °		70.5 °	57.6	29.9	47.5	4.5	7.9	110.3	
	55cm	700c		73.0 °		71.0 °	59.2	29.9	47.5	4.5	7.6	111.5	
Lift+	S	26"	42.0	65.5 °	21.0	69.5 °	61.2	28.6	49.5	5.0	7.3	109.0	69.5
	M	26"	45.7	65.5 °	21.0	69.5 °	62.0	28.6	49.5	5.0	7.3	109.8	71.7
	L	26"	53.3	65.5 °	26.0	69.5 °	65.0	28.6	49.5	5.0	7.3	112.3	78.0
	S Lowstep	26"	34.3	65.5 °	20.0	69.5 °	59.2	28.6	49.5	5.0	7.3	107.1	64.4
	M Lowstep	26"	42.0	65.5 °	21.0	69.5 °	61.2	28.6	49.5	5.0	7.3	109.0	69.1
Shift	14.5"	26"		65.5 °	13.7	69.0 °	59.4	28.2	49.5	5.0	7.4	108.0	67.0
	16.5"	26"		65.5 °	17.2	69.0 °	61.1	28.2	49.5	5.0	7.4	109.5	70.6
	18.5"	26"		65.5 °	17.2	69.0 °	62.0	28.2	49.5	5.0	7.4	110.3	72.7
	21"	26"		65.5 °	22.2	69.0 °	64.9	28.2	49.5	5.0	7.4	113.0	76.8
Shift WSD	13.5"	26"		65.5 °	16.2	69.0 °	59.1	28.2	49.5	5.0	7.4	107.5	50.3
	16.5"	26"		65.5 °	17.2	69.0 °	61.1	28.2		5.0	7.4	109.5	50.3
	19"	26"		65.5 °	19.7	69.0 °	63.3	28.2	49.5	5.0	7.4	111.5	50.3
Verve	15"	700c		73.0 °	10.0	70.5 °	57.2	28.5	46.5	5.1	7.0	109.0	71.5
	17.5"	700c		72.5 °	11.5	70.5 °	57.8	28.5	46.5	5.1	7.0	109.2	75.3
	20"	700c		72.0 °	12.5	70.5 °	59.4	28.5	46.5	5.1	7.0	110.3	78.9
	22.5"	700c		71.5 °	15.5	71.0 °	61.3	28.5	46.5	5.1	6.6	111.1	83.5
	25"	700c		71.5 °	20.5	71.0 °	62.0	28.5	46.5	5.1	6.6	111.8	89.0
Verve WSD	13"	700c		73.0 °	17.0	70.5 °	56.0	28.5	46.5	5.1	6.9	108.3	44.8
	16"	700c		72.5 °	18.0	70.5 °	57.5	28.5	46.5	5.1	7.0	109.2	44.8
	19"	700c		72.0 °	18.0	70.5 °	60.0	28.5	46.5	5.1	7.0	111.0	44.8
T900	18.5" Front	26"		72.5 °	19.5	73.0 °	57.7	28.7	43.5	5.5	4.4	177.1	76.1

14.5" Rear

26"

72.5°

22.7

28.6

55.9